

Receiver Selection Guide

	Features		Models	Input Voltage	Camera Output Voltage	Lens Output Voltage	Pan/Tilt Output Voltage	Enclosure Output Voltage
Coaxitron Receiver	Indoor	Fixed Speed, No Presets	IRD2024	24 VAC	24 VAC	8 VDC	24 VAC	Customer Supplied
	Outdoor	Fixed Speed, No Presets	ERD2200	120/230 VAC	24 VAC	8 VDC	24/120/230 VAC	120/230 VAC
			CX9024RX-PP	24 VAC	24 VAC	8 VDC	24 VAC	Customer Supplied
		Fixed Speed, with Presets	CX9024RX-PP220	230 VAC	24 VAC	8 VDC	24 VAC	Customer Supplied
			CX9115RX-PP	120 VAC	120 VAC	8 VDC	120 VAC	Customer Supplied
			CX9220RX-PP	230 VAC	230 VAC	8 VDC	230 VAC	Customer Supplied
RS-422 ("P") Receiver	Outdoor	Fixed Speed, with Presets	ERD97P21-U	24/120/230 VAC	24/120/230 VAC	24/120/230 VAC*	24/120/230 VAC*	24/120/230 VAC (Same as input)

*No voltage step-up possible; 230 VAC input can not step down to 120 VAC.
For selection of Legacy® receivers, refer to the *Legacy Pan/Tilt Systems Selection Guide*.